



### 9" Diameter (2.80/2.50-4) Cart Wheel

Ideally suited for light service delivery carts, 4 wheeled garden carts and wagons.

Product No.	Tire Dia.	Tire Width	Tread	Rim Dia.	Hub Width	Capacity
Wh-15	8.75"	2.375"	Jag	4"	1.75"	175 lbs

**Standard:** 3pc 1.75" centered wheel hub with 5/8" ball bearings

**Options:** 1/2", 5/8", or 3/4" bearings



### 9" Diameter (2.80/2.75-4) Cart Wheel

Designed for medium duty beverage carts and wagons.

Product No.	Tire Dia.	Tire Width	Tread	Rim Dia.	Hub Width	Capacity
Wh-28	8.75"	2.750"	Jag	4"	4.00"	200 lbs
Wh-29	8.75"	3.00"	Rib	4"	4.00"	175 lbs

**Standard:** 1pc 4" centered wheel hub with 5/8" ball bearings & grease fitting

**Options:** Wheel Hubs - 3", 4" centered, 2.25" Offset with 1/2", 5/8", or 3/4" bearings



### 10" Diameter (4.10/3.50-4) Hand Truck Wheel

This wheel size serves many applications, from Hand Trucks to Power Washers.

Product No.	Tire Dia.	Tire Width	Tread	Rim Dia.	Hub Width	Capacity
W-24	10.00"	3.25"	Sawtooth	4"	4.00"	250 lbs
W-25	10.00"	3.25"	Sawtooth	4"	2.250"	250 lbs

**Standard:** 1pc 4" centered wheel hub with 5/8" ball bearings & grease fitting

**Options:** Wheel Hubs - 3", 4" centered, 2.25" Offset with 1/2", 5/8", or 3/4" bearings



### 10" Diameter (10x3.00-4) Hand Truck Wheel

This wheel is mainly used on Hand Trucks and Outdoor Equipment.

Product No.	Tire Dia.	Tire Width	Tread	Rim Dia.	Hub Width	Capacity
W-34	10.00"	3.25"	Diamond	4"	2.250"	250 lbs

**Standard:** 1pc 2.25 Offset Wheel Hub with 5/8" ball bearings

**Options:** Wheel Hubs - 3", 4" centered with 1/2", 5/8", or 3/4" bearings




### 12" Diameter (12/5.00-6) Hand Truck Wheel (Heavy Duty)

Wheel is designed for handling heavy products over curbs and obstacles.

Product No.	Tire Dia.	Tire Width	Tread	Rim Dia.	Hub Width	Capacity
Wh-124	12.250"	4.00"	Rib	6"	2"	350 lbs

**Standard:** 1pc 2" centered wheel hub with 3/4" ball bearings

**Optional:** 1/2", 5/8", or 3/4" roller bearings



### 14" Diameter 4.80/4.00-8 Wheel (Light Duty)

Light weight replacement wheel for light duty wheelbarrows and wagons, etc.

Product No.	Tire Dia.	Tire Width	Tread	Rim Dia.	Hub Width	Capacity
W-2	14.250"	3.75"	Rib	8"	6"	250 lbs.

**Standard:** 1pc centered wheel hub with 5/8" ball bearings & grease fitting

**Options:** Wheel Hubs - 3", 4" centered with 1/2", 5/8", or 3/4" bearings



### 15" Diameter 480/400-8 Wheel (Standard Duty)

Great replacement wheel for 5 and 6 cubic feet wheelbarrows. Ideal for new equipment, construction rentals, maintenance crews equipment, landscapers, homeowners, etc.

Product No.	Tire Dia.	Tire Width	Tread	Rim Dia.	Hub Width	Capacity
W-1	15.50"	3.75"	Rib	8"	6"	400 lbs.

**Standard:** 1pc centered wheel hub with 5/8" ball bearings & grease fitting

**Options:** Wheel Hubs - 3", 4" centered with 1/2", 5/8", or 3/4" bearings



### 15" & 16" Diameter 480/400-8 Wheel (Heavy Duty)

This Heavy Duty Wheel is designed to handle loads up to 595 lbs. Ideal for construction trades that manually haul heavy loads of concrete, earth and stone.

Product No.	Tire Dia.	Tire Width	Tread	Rim Dia.	Hub Width	Capacity
W-1HD 500	15.50"	3.75"	Rib	8"	6"	595 lbs.
W-11	16.25"	3.875"	Rib	8"	6"	550 lbs.

**Standard:** 1pc centered wheel hub with 5/8" roller bearings & grease fitting

**Options:** Wheel Hubs - 3", 4" centered with 1/2", 5/8", or 3/4" bearings



### 16" Diameter 480/400-8 Diamond Tread Wheel (Standard Duty)

Diamond tire tread improves equipment's traction when operated in rough and uneven areas.

Product No.	Tire Dia.	Tire Width	Tread	Rim Dia.	Hub Width	Capacity
W-13	16.250"	3.875"	Rib	8"	6"	480 lbs

**Standard:** 1pc centered wheel hub with 5/8" ball bearings & grease fitting

**Options:** Wheel Hubs - 3", 4" centered with 1/2", 5/8", or 3/4" bearings



### 16" Diameter 480/400-8 Smooth Tread Wheel (Standard Duty)

Smooth tire tread reduces compaction while rolling on soft surfaces. Ideal for golf courses and roofing equipment

Product No.	Tire Dia.	Tire Width	Tread	Rim Dia.	Hub Width	Capacity
W-12	16.750"	3.750"	Smooth	8"	6"	450 lbs

**Standard:** 1pc centered wheel hub with 5/8" ball bearings & grease fitting

**Optional:** Wheel Hubs - 3", 4" centered with 1/2", 5/8", or 3/4" bearings

\*All of the above Wheelbarrow Wheel Assemblies with standard 6" wheel hubs include: 5/8" x 10.375" zinc plated cold rolled steel axle with washers & cotter pins.