



8" Diameter 8/300-4 Wheel (caster wheel)

This is a common wheel used on front rotary mowers. Please check your wheel dimensions prior to ordering. Product # 573-4 tire has rounded corners to prevent cutting into turf when fork rapidly swivels.

Product No.	Tire Dia.	Tire Width	Seat	Tread	Rim Dia.	Hub Width	Capacity
575-3	7.75"	3.00"	2.25"	Smooth	4.00"	4.00"	175 lbs
573-4	8.00"	3.00"	2.50"	Smooth	4.00"	4.00"	175 lbs
573-5	8.25"	3.00"	2.375"	Smooth	4.00"	4.00"	180 lbs

Standard: Split rims fastened to a 4" centered hub with 3/4" roller cage bearing, end caps and grease fitting

Hub Options: 2.50", 3.00", 3.250", 3.50" centered hub with 3/4" roller bearings, retainers and grease fitting



9" Diameter 9/3.50-4 (caster wheel)

Our caster wheels offer great insurance against flats on equipment from Walk Behind Mowers to Zero Turn Mowers our that cannot afford downtime.

Product No.	Tire Dia.	Tire Width	Seat	Tread	Rim Dia.	Hub Width	Capacity
575	9.00"	3.50"	2.75"	Smooth	4.00"	4.00"	225 lbs
575-1	9.00"	3.375"	2.50"	Smooth	4.00"	4.00"	225 lbs
575-2	9.00"	3.75"	3.00"	Smooth	4.00"	4.00"	250 lbs

Standard: Split rims fastened to a 4" centered hub with 3/4" roller cage bearing, end caps and grease fitting

Hub Options: 2.50", 3.00", 3.250", 3.50" centered hub with 3/4" roller bearings, retainers and grease fitting



10" Diameter 4.10/3.50-4 (caster wheel)

Wheel is designed for fixed and swivel type forks that are equipped on many types of landscaping equipment requiring a 10" diameter wheel.

Product No.	Tire Dia.	Tire Width	Seat	Tread	Rim Dia.	Hub Width	Capacity
565	10.00"	3.125"	2.50"	Rib	4.00"	4.00"	250 lbs
565-1	10.00"	3.625"	2.75"	Rib	4.00"	4.00"	250 lbs

Standard: Split rims fastened to a 4" centered hub with 3/4" roller cage bearing, end caps and grease fitting

Hub Options: 2.50", 3.00", 3.250", 3.50" centered hub with 3/4" roller bearings, retainers and grease fitting



10" Diameter 4.10-4.00-6 (caster wheel)

This wheel is designed for heavy front and rear mount cutting decks. Low profile tire and heavy duty split rim produce a lightweight cost efficient alternative to air and or heavy foam filled tired wheels.

Product No.	Tire Dia.	Tire Width	Seat	Tread	Rim Dia.	Hub Width	Capacity
576	10.00"	4.00"	3.00"	smooth	6.00"	4.00"	300 lbs

Standard: 2.50", 3.00", 3.250", 3.50" centered hub with 3/4" roller bearings, retainers and grease fitting

* Outside Diameter of all bearings is 1 3/8" to fit standard and optional hubs.

Tires, Wheel Rims, Hubs and Bearings can be ordered separately. Please view Product Specifications chart and/or Wheel Rims chart to help you locate the components you require.



11" Diameter 11/4.00-5 (caster wheel)

This wheel assembly is common on medium size mowing equipment. Flats are more prevalent on these types of machines from use and abuse, residential curbs, trailer ramps, litter and lawns debris, etc;

Product No.	Tire Dia.	Tire Width	Seat	Tread	Rim Dia.	Hub Width	Capacity
577	10.50"	4.25"	3.375"	Smooth	5.00"	4.00"	300 lbs
577-1	11.00"	3.75"	3.00"	Smooth	5.00"	4.00"	275 lbs

Standard: Split rims fastened to a 4" centered hub with 3/4" roller cage bearing, end caps and grease fitting



12" & 13" Diameter 12/5.00-6 / 13/5.00-6 (caster wheel)

Both the 12" and 13" rib tread wheel assemblies are suited for zero turn mowers and other implement equipment. Please check your clearance in the fork before ordering one size versus the other.

Product No.	Tire Dia.	Tire Width	Seat	Tread	Rim Dia.	Hub Width	Capacity
875	12.25"	4.00"	3.25"	Rib	6.00"	2.00"	325 lbs
876	13.25"	4.00"	3.50"	Rib	6.00"	2.00"	350 lbs

Standard: 1 pc wheel rim - 2" centered hub with 3/4" roller bearing, retainers and grease fitting

Hub Options: Split rims fastened to a 4" centered hub with 3/4" roller cage bearing, end caps and grease fitting



13" Diameter 13/6.50-6 (caster wheel)

These wheels also vary in overall diameter, please check with your existing tire or wheel to see which wheel is best suited for your equipment. These tires provide a soft ride while handling a heavier load.

Product No.	Tire Dia.	Tire Width	Seat	Tread	Rim Dia.	Hub Width	Capacity
975	12.50"	5.00"	3.375"	Rib	6.00"	2"	375 lbs
975-1	13.00"	5.75"	4.00"	Smooth	6.00"	2.75"	400 lbs

Standard: 1 pc wheel rim - 3" centered hub with 3/4" roller bearing and retainers



16" Diameter 16/6.50-6 (drive wheel)

Aggressive Traction Wheel has many applications from light capacity trailers to small tractors.

Product No.	Tire Dia.	Tire Width	Seat	Tread	Rim Dia.	Hub Width	Capacity
525	15.50"	6.50"	5.375	Bell	8.00"	4.00"	575 lbs

Standard: 1 pc wheel rim - 4" offset hub with 3/4" or 1" roller cage bearing, end caps and grease fitting

* Outside Diameter of all bearings is 1 3/8" to fit standard and optional hubs.

Tires, Wheel Rims, Hubs and Bearings can be ordered separately. Please view Product Specifications chart and/or Wheel Rims chart to help you locate the components you require.